

ZEE 2™



RESIDENTIAL

MODELS:

2342KW 23hp, 42" Deck

2348KW 23hp, 48" Deck

2354KW 23hp, 54" Deck



Zee 2 - 2348KW shown

THE MOWER WITH MORE MUSCLE FOR YOUR MONEY.


- **High Horsepower** - A 23 horsepower engine from Kawasaki* to power through thick grass up to 3.1 acres per hour.
- **Elite Cutting System** - Offered in three cutting widths (42", 48", and 54"), the Elite Deck easily cuts large volumes of grass and provides an attractive after-cut appearance.
- **7-Stage Deck Height** - Allows you to quickly and easily adjust mowing height for different applications.
- **Hydro-Gear® ZT-2800 Transaxles** - Proven and reliable transmissions with an external oil filter for easier maintenance and extended system life.
- **Quick-Lift Lock** - Allows you to quickly raise the deck to avoid objects and locks the deck in travel height for transporting or storing.
- **Steel Fenders** - Built with 14-gauge steel, the fenders protect the body and fuel tank from damage.
- **Industry Leading Warranty** - Backed with a three year warranty with unlimited hours of residential use and industry leading lifetime warranties.



Steel Fenders - Protects fuel tank from sun and impact damage



Commercial Forks - Greaseable and lifetime warranty against breakage



Hydro-Gear® ZT-2800 - Smooth operation and fully serviceable



Comfort Ride - Plush cushioned seat with armrests for extra comfort



42", 48", & 54" Elite Cutting System - Formed and welded 10-ga deck shell

3 YEAR
BUMPER-TO-BUMPER
WARRANTY*

*Unlimited hour limited residential warranty, see dealer for complete warranty details



ZEE 2™



	42" Deck	48" Deck	54" Deck
Model	2342KW	2348KW	2354KW
Engine			
Manufacturer	Kawasaki® FR		
Horsepower	23		
Displacement	726cc		
Air-cleaner	2 stage		
Cooling	Air-cooled		
Starter	Electric		
Engine warranty	3-Year		

Drive System			
Dual hydrostatic	Hydro-Gear® ZT-2800 transaxles (internal expansion tank)		
Ground speed	7 mph		
Parking brake	Integrated in transaxle		
Towing capacity	100 lbs		

Mower Deck			
Deck size	42"	48"	54"
Acres/hour*	2.4	2.7	3.1
Cutting height	1.5" - 4.5"		
Deck height adjustments	Manual lift, 1/2" increments		
Deck Quick-Lift	Integrated		
Deck engagement	Ogura® 87 ft-lbs		
Construction	10 ga formed & welded		
Blades	3 - 15.25" x 2.5"	3 - 17.25" x 2.5"	3 - 19.25" x 2.5"
Blade tip speed (approximate)	18,500 fpm		
Spindles	.75" effective diameter machined shaft		
Spindle housings	1pc keyless sealed cast aluminum		
Anti-scalp rollers	4		
Pulleys	Vented split 3/16" steel deep groove		

General			
Battery	12 Volt, 300cca		
Digital display	hour meter		
Fuel capacity	4 gallons		
Rear tires	20 x 8-10 GrassMaster	20 x 10-8 GrassMaster	
Front tires	13 x 6.5-6		
Frame	Welded 1" x 2", 2" x 2" tube, 10 ga formed		
Floor-pan	Removable, steel		
Seat	20" padded seat w/ armrests		

Dimensions			
Overall height	47"		
Overall width (with chute)	51.5"	57.5"	64"
Overall length	76"		
Weight	730 lbs	750 lbs	763 lbs